



P.C.B LAYOUT
BOTTOM VIEW

注：“*”口表示关键尺寸(7个).

SPECIFICATIONS

1. LIFE TEST:WITHOUT LOADING 10000cycles at a speed of 15-18cycles
2. CONTACT RESISTANCE:100mΩmax
3. INSULATION RESISTANCE:100MΩmin
4. DIELETRIC STRENGTH:500V AC FOR 1MIN
5. OPERATING TEMPERATURE:-16°C--+60°C
6. RATING:.0.5A 30V DC
7. FUNCTION:2P2T
8. TIMING:NON-SHORTING
9. OPERATING FORCE:400gf±100gf

NO.	PARTS	MATERIALS	Q'TY
9	CONTACT CLIP	PBS C5210R-EH	2
8	TERMINAL	BRASS STRIP	6
7	BASE	PHENOLIC RESIN	1
6	FRAME	STEEL STRIP	1
5	SPRING PLATE	PBS STRIP	1
4	CAM STICK	PBS WIRE	1
3	SPRING	STEEL WIRE	1
2	BLOCK	STEEL STRIP	1
1	KNOB	PBT	1

TOLERANCE UNLESS SPECIFIED					
WITHIN 1.5mm	: ±0.1mm	A	2008.6.8	初版	张小姐
OVER 1.5mm	: ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
TITLE : PUSH SWITCH			UNIT : mm	DRWG NO.:	
MODEL:			SCALE: 3:1	DWN.	张小姐 2008.6.8
東莞市高迪電子有限公司 KDRR Electronic Switch JacK Co.,Ltd			CHK'D	刘工	2008.6.8
			APPD.		