



SPECIFICATIONS

1. LIFE TEST: WITHOUT LOADING 10000cycles at a speed of 15-18cycles
2. CONTACT RESISTANCE: 100mΩmax
3. INSULATION RESISTANCE: 100MΩmin
4. DIELECTRIC STRENGTH: 500V AC FOR 1 MIN
5. OPERATING TEMPERATURE: -40°C - +70°C
6. RATING: DC 1.0A 12V
7. FUNCTION: 2P2T
8. TIMING: NON-SHORTING
9. OPERATING FORCE: 400gf ± 100gf

注：“*”号表示关键尺寸(7个).

9	CONTACT CLIP	PBS C5210R-EH	2	Ag CLAD (0.1um-0.3um)
8	TERMINAL	BRASS STRIP	6	Ag PLATED (0.1um-0.3um)
7	BASE	PHENOLIC RESIN	1	NATURAL
6	FRAME	STEEL STRIP	1	Ni PLATED (Cu:0.2-0.4um;Ni:1.0-1.5um)
5	SPRING PLATE	PBS STRIP	1	NATURAL
4	CAM STICK	PBS WIRE	1	NATURAL
3	SPRING	STEEL WIRE	1	Ni PLATED (Cu:0.2-0.4um;Ni:1.0-1.5um)
2	BLOCK	STEEL STRIP	1	Ni PLATED (Cu:0.2-0.4um;Ni:1.0-1.5um)
1	KNOB	NYLON	1	BLACK
NO.	PARTS	MATERIALS	Q'TY	

TOLERANCE					
UNLESS SPECIFIED					
WITHIN 1.5mm	: ±0.1mm	A	2008.6.8	初版	张小姐
OVER 1.5mm	: ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
TITLE : PUSH SWITCH			UNIT : mm	DRWG NO.:	
MODEL:			SCALE: 3:1	DWN. 张小姐	2008.6.8
東莞市高迪電子有限公司 KDRR Electronic Switch JacK Co.,Ltd				CHK'D 刘工	2008.6.8
				APPD.	