

技术参数
 轴方向数: 两向
 额定电压: DC 12V
 额定电流: 15A
 初期接触阻值: 50mΩ
 绝缘阻抗: 100MΩ
 耐电压: AC 300V 1分钟
 开关动作力: 600 ± 150gf
 开关全行程: 2.0 ± 0.2mm
 接触行程: 1.6 ± 0.3mm
 轴向间隙: 0.4mm
 按压寿命: 25000次




E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	SUS	Ag plated
B	CASE	1	LCP	Black
A	Knob	1	PA46	Black
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

 **东莞市高迪电子有限公司**
 Dong Guan KDRR Electronic Switch Jack Co., Ltd.

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	07/30/13		MODLE	Multi Function SWITCH
CHECKED BY:	DATE	FINISH	DWG NO.	SIZE
Jacky Chen	07/30/13			A4
APPROVED BY:	DATE	SCALE	PART NO.	VER
Tony Kao	07/30/13	1 : 1		R1
		SHEET NO.	1 of 1	

1	更新材質	Jack	073013
ITEM NO.	DESCRIPTION	DRAWN	DATE

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S  UNITS MM