



SPECIFICATIONS

Rating	0.1A 12V DC
Insulation Resistance	50M Ω Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100m Ω Max.
Operating Life	50,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	SUS	Ag plated
B	CASE	1	LCP	Black
A	Knob	1	PA46	Black



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

DRAWN BY: Jack Lu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao

DATE: 07/30/13
 DATE: 07/30/13
 DATE: 07/30/13

MAT'L
 FINISH
 SCALE: 1:1
 SHEET NO. 1 of 1

TITLE: SWITCH
 MODLE: Multi Function SWITCH
 DWG NO.
 PART NO.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS: MM

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新材質	Jack	073013

SIZE: A4
 VER: R1