



SPECIFICATIONS

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: $100 \text{m}\Omega$ max
- (3) INSULATION RESISTANCE: $100 \text{M}\Omega$ min
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C - $+60^{\circ}\text{C}$
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: $180 \text{gf} \pm 50 \text{gf}$

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
8								
7								
6								
5	SPRING	SUS304	1		A	2016-10-14	初版	
4	CAM STICK	SUS304	1					
3	CASE	PA66/BRASS STRIP	1					
2	COVER	PA66+15%F.G	1					
1	KNOB	PA66+15%F.G/PBS STRIP	1					
				TITLE : VERTICAL PUSH SWITCH			UNIT : mm	DRWG NO.:
				MODEL:			SCALE: 5:1	DWN. 2016-10-14
							CHK'D	2016-10-14
							APPD.	