



SCHEMATIC (NON-SHORTING)

### SPECIFICATIONS

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: 100mΩ max
- (3) INSULATION RESISTANCE: 100MΩ min
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C +60°C
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: 180gf ± 50gf

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	A		初版	
8				WITHIN 1.5mm : ±0.1mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	
7				OVER 1.5mm : ±0.2mm	2016-10-14		APPD.	
6				TITLE : VERTICAL PUSH SWITCH				UNIT : mm
5	SPRING	SUS304	1	MODEL:				SCALE: 5:1
4	CAM STICK	SUS304	1	DRWG NO.:				DWN. 吴开庆
3	CASE	PA66/BRASS STRIP	1	DONGGUANGAODIELECTRONICS CO.,LTD.				2016-10-14
2	COVER	PA66+15%F.G	1	CHK'D 曾小伟				2016-10-14
1	KNOB	PA66+15%F.G/PBS STRIP	1	APPD.				