



SPECIFICATIONS

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: 100mΩmax
- (3) INSULATION RESISTANCE: 100MΩmin
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C - +60°C
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: 180gf ± 50gf

				TOLERANCE UNLESS SPECIFIED			
				WITHIN 1.5mm : ±0.1mm		OVER 1.5mm : ±0.2mm	
				A	2016-10-14	初版	
				ISSUE	DATE	DESCRIPTIONS OF REVISION	
				TITLE : VERTICAL PUSH SWITCH			UNITS : mm
				MODEL:			SCALE: 5:1
				東莞市高迪電子有限公司			DRWG NO.:
				DONGGUANGAODIELECTRONICS CO.,LTD.			DWN.
							2016-10-14
							CHK'D
							2016-10-14
							APPD.
8							
7							
6							
5	SPRING	SUS304	1	NATURAL			
4	CAM STICK	SUS304	1	NATURAL			
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED			
2	COVER	PA66+15%F.G	1	BLACK			
1	KNOB	PA66+15%F.G/PBS STRIP	1	BLACK/Ag CLAD			
NO.	PARTS	MATERIALS	Q'TY				