



**SPECIFICATIONS**

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: 100mΩ max
- (3) INSULATION RESISTANCE: 100MΩ min
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C - +60°C
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: 180gf ± 50gf

|     |           |                       |      |                |   |       |            |                          |  |            |
|-----|-----------|-----------------------|------|----------------|---|-------|------------|--------------------------|--|------------|
| 8   |           |                       |      |                |   |       |            |                          |  |            |
| 7   |           |                       |      |                |   |       |            |                          |  |            |
| 6   |           |                       |      |                |   |       |            |                          |  |            |
| 5   | SPRING    | SUS304                | 1    | NATURAL        |   |       |            |                          |  |            |
| 4   | CAM STICK | SUS304                | 1    | NATURAL        |   |       |            |                          |  |            |
| 3   | CASE      | PA66/BRASS STRIP      | 1    | GREY/Ag PLATED |   |       |            |                          |  |            |
| 2   | COVER     | PA66+15%F.G           | 1    | BLACK          |   |       |            |                          |  |            |
| 1   | KNOB      | PA66+15%F.G/PBS STRIP | 1    | BLACK/Ag CLAD  |   |       |            |                          |  |            |
| NO. | PARTS     | MATERIALS             | Q'TY |                |   |       |            |                          |  |            |
|     |           |                       |      |                | TOLERANCE UNLESS SPECIFIED                              |       |            |                          |  |            |
|     |           |                       |      |                | WITHIN 1.5mm : ±0.1mm                                   | A     | 2016-10-14 | 初版                       |  |            |
|     |           |                       |      |                | OVER 1.5mm : ±0.2mm                                     | ISSUE | DATE       | DESCRIPTIONS OF REVISION |  | APPD.      |
|     |           |                       |      |                | TITLE : VERTICAL PUSH SWITCH                            |       | UNIT : mm  | DRWG NO.:                |  |            |
|     |           |                       |      |                | MODEL:  |       | SCALE: 5:1 | DWN.                     |  | 2016-10-14 |
|     |           |                       |      |                | <b>东莞市高迪电子有限公司</b><br>DONGGUANGAODIELECTRONICS CO.,LTD. |       |            | CHK'D                    |  | 2016-10-14 |
|     |           |                       |      |                |   |       |            | APPD.                    |  |            |