


P.C.B MOUNTING PATTERN
BOTTOM VIEW

SPECIFICATIONS

- 1. Rating : DC 30V 0.1A
- 2. Circuit : 2P2T
- 3. Timing : Non-Shorting
- 4. Operating force : 200 ± 100gf
- 5. Life test : 10,000 cycles
- 6. Operating Mode : Non-Lock



SCHEMATIC

6	CONTACT CLIP	2	PHOSPHOR BRONZE	Ag-Plated
5	SPRING	1	SUS	NATURAL
4	TERMINAL	6	BRASS	Ag-Plated
3	CASE	1	PBT	BLACK
2	COVER	1	POM	WHITE
1	KNOB	1	POM	BLUE
NO.	DESCRIPTION	QTY	MATERIAL	REMARK

东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	10/23/15			
CHECKED BY:	DATE	FINISH	MODLE	PUSH SWITCH
Jacky Chen	10/23/15			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	10/23/15	1 : 1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R2

ITEM NO	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	102315
1	更新版面	Jack	020515

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 - 15	±0.3
Above 15 - 30	±0.4
Above 30 - 50	±0.5
Angle	±0.3°

3RD. ANGEL'S UNITS MM