

NOTE:


- 1. : SELF-LOCK
- 2. :NON-LOCK



SCHEMATIC



SPECIFICATIONS

- 1. Rating : DC 30V 0.1A
- 2. Circuit : 2P2T
- 3. Timing : Non-Shorting
- 4. Operating force : 160 ± 50gf
- 5. Life test : 10,000 cycles



P.C.B MOUNTING PATTERN

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	CONTACT(CLIP)	2	PHOSPHOR BRONZE	Ag-Plated
5	SPRING	1	STEEL	
4	TERMINAL	6	BRASS	Ag-Plated
3	BOTTOM CASE	1	PA66	BLACK
2	COPING CASE	1	PA66	WHITE
1	KNOB	1	POM	GREEN



view A
scale 1:1

ITEM NO	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	102915
1	新增PIN編號	Jack	101215


东莞市高迪电子有限公司
 Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 - 15	±0.3
Above 15 - 30	±0.4
Above 30 - 50	±0.5
Angle	±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SIZE
Jack Lu	10/23/15		SWITCH	A4
CHECKED BY:	DATE	FINISH	MODLE	VER
Jacky Chen	10/23/15		PUSH SWITCH	R2
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	10/23/15	1:1		
		SHEET NO.	PART NO.	
		1 of 1		