



项目		尺寸(mm)				
系列	型号	L	M	A	S1	S2
0M	T1	35.5	25.5	9.4	7.4	8.0
1M	T1	42.3	30.1	11.8	11.0	9.0
2M	T1	50.2	37.7	15	13	13
3M	T1	59.7	44.3	18.7	17	15

### 产品主要技术参数

特性	参数
锁紧方式	推拉自锁式
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68

东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19		MODLE	T1插头
CHECKED BY:	DATE	FINISH	DWG NO.	
Jacky Chen	12/13/19		PART NO.	
APPROVED BY:	DATE	SCALE	1 : 1	
Tony Kao	12/13/19	SHEET NO.	1 of 1	

ITEM NO. DESCRIPTION DRAWN DATE

SIZE  
A4  
VER  
R1