



项目		尺寸(mm)									面板开孔尺寸(mm)		
系列	型号	A	B	L	N	M	E	S1	S2	e	Ws	Ø	种类
00B	T2	8	10.2	18.1	15	9	2.9	6.3	9	M7*0.5	6.4	7.1	A
0B	T2	10	12.5	20.8	18.4	11.2	4.2	8.2	11	M9*0.5	8.3	9.1	A
1B	T2	14	16	25.2	22.6	12.5	5.4	10.5	14	M12*1.0	10.6	12.1	A
2B	T2	18	19.2	24.7	22.5	13.8	6.0	13.5	17	M15*1.0	13.6	15.1	A
3B	T2	21	25.4	32.1	29.1	17.0	5.8	16.5	22	M18*1.0	16.6	18.1	A

### 产品主要技术参数

特性	参数
锁紧方式	推拉自锁式
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP50

东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY: Jack Lu DATE: 12/13/19  
CHECKED BY: Jacky Chen DATE: 12/13/19  
APPROVED BY: Tony Kao DATE: 12/13/19

MAT'L	TITLE	CONNECTOR
FINISH	MODLE	T2插头
SCALE	DWG NO.	
SHEET NO.	PART NO.	

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4  
VER R1