



项目		尺寸(mm)										
系列	型号	L	B	N	I	H	A	D	d	R	J	b
00B	Z11	18.5	8.9	7.5	7.0	3.5	6.8	11.5	0.7	5.08	5	0.5
0B	Z11	25.5	13.3	11.7	12.7	6.7	9	14.6	0.7	7.62	3	0.6
1B	Z11	26.8	13.3	12.6	14	7.5	11	16.67	0.7	7.62	3	0.6

### 产品主要技术参数

特性	参数	特性	参数
锁紧方式	推拉自锁式	盐雾试验	96hr
工作温度	-55°C~+125°C	抗冲击性能	100g,6ms
最大潮湿	在60°C/140°F时最高达到95%	机械寿命	5000次
屏蔽性能	75dB(10MHz) 40dB(1GHz)	防护等级	IP68
抗振动性能	15g[10Hz~2000Hz]		

东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19	FINISH	MODLE	Z11插座
CHECKED BY:	DATE	SCALE	DWG NO.	
Jacky Chen	12/13/19	1 : 1	PART NO.	
APPROVED BY:	DATE	SHEET NO.		
Tony Kao	12/13/19	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4  
VER R1