



项目		尺寸(mm)													
系列	型号	L	K	A	N	R	S1	e	I	H	E	J	D	d	b
00B	Z12	18.5	9	10	7.6	5.08	9	M7*0.5	7	3.5	3	5	11.5	0.7	0.5
0B	Z12	25	13.3	12	11.7	7.62	10	M9*0.6	12.7	6.7	3.5	3	14.6	0.7	0.6
1B	Z12	27	13.3	14	12.6	7.62	13	M11*1.0	14	7.5	5.0	3	16.6	0.7	0.6

产品主要技术参数

特性	参数	特性	参数
锁紧方式	推拉自锁式	盐雾试验	96hr
工作温度	-55°C~+125°C	抗冲击性能	100g,6ms
最大潮湿	在60°C/140°F时最高达到95%	机械寿命	5000次
屏蔽性能	75dB(10MHz) 40dB(1GHz)	防护等级	IP68
抗振动性能	15g[10Hz~2000Hz]		

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19		MODLE	Z12插座
CHECKED BY:	DATE	FINISH	DWG NO.	
Jacky Chen	12/13/19		SHEET NO.	1 of 1
APPROVED BY:	DATE	SCALE	PART NO.	
Tony Kao	12/13/19	1:1		

ITEM NO.	DESCRIPTION	DRAWN	DATE