



项目		尺寸(mm)								面板开孔尺寸(mm)		
系列	型号	A	B	E	L	M	P	S1	e	Ws	Ø	种类
0K	Z13	18	18	2.0	22.5	3.5	7	12.5	M14*1.0	12.6	14.1	A
1K	Z13	20	20	5.5	28.4	3.0	10	14.5	M16*1.0	14.6	16.1	A
2K	Z13	25	25	5.0	29.0	3.5	10	18.5	M20*1.0	18.6	20.1	A

### 产品主要技术参数

特性	参数
锁紧方式	推拉自锁
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68

东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu	DATE: 12/13/19	MAT'L	TITLE: CONNECTOR
CHECKED BY: Jacky Chen	DATE: 12/13/19	FINISH	MODLE: Z13插座
APPROVED BY: Tony Kao	DATE: 12/13/19	SCALE: 1:1	DWG NO.
		SHEET NO: 1 of 1	PART NO.

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE: A4  
VER: R1