



项目		尺寸(mm)							面板开孔尺寸(mm)		
系列	型号	L	M	A	B	S1	E	e	Ws	Ø	种类
0M	Z13	21	8.9	11.9	12.9	8.2	4.5	M9*0.5	8.3	9.1	A
1M	Z13	25	10	16.0	15.5	10.5	5.5	M12*1.0	10.6	12.1	A
2M	Z13	27	11	20	18.5	13.5	6.5	M15*1.0	13.6	15.1	A
3M	Z13	31	12	25	23.5	16.5	6	M18*1.0	16.6	18.1	A

产品主要技术参数

特性	参数
锁紧方式	推拉自锁式
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19		MODLE	Z13插座
CHECKED BY:	DATE	FINISH	DWG NO.	
Jacky Chen	12/13/19		PART NO.	
APPROVED BY:	DATE	SCALE	1:1	
Tony Kao	12/13/19	SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE
A4
VER
R1