



| 项目 | | 尺寸(mm) | | | | | | | | | 面板开孔尺寸(mm) | | |
|-----|----|--------|------|------|------|------|-----|------|----|---------|------------|------|----|
| 系列 | 型号 | A | B | L | N | M | E | S1 | S3 | e | Ws | Ø | 种类 |
| 00B | Z1 | 8 | 10.2 | 15.9 | 13.7 | 1.0 | 6.0 | 6.3 | 9 | M7*0.5 | 6.4 | 7.1 | A |
| 0B | Z1 | 10 | 12.5 | 21.3 | 16.8 | 1.25 | 7.0 | 8.2 | 11 | M9*0.6 | 8.3 | 9.1 | A |
| 1B | Z1 | 14 | 16 | 23.2 | 18.7 | 1.5 | 7.5 | 10.5 | 14 | M12*1.0 | 10.6 | 12.1 | A |
| 2B | Z1 | 18 | 19.2 | 24.8 | 20 | 2 | 8.0 | 13.5 | 17 | M15*1.0 | 13.6 | 15.1 | A |
| 3B | Z1 | 21 | 25.4 | 30.7 | 25 | 1.85 | 11 | 16.5 | 22 | M18*1.0 | 16.6 | 18.1 | A |
| 4B | Z1 | 28 | 34 | 37 | 29 | 2.5 | 12 | 23.5 | 30 | M25*1.0 | 23.6 | 25.2 | A |

产品主要技术参数

| 特性 | 参数 |
|-------|------------------------|
| 锁紧方式 | 推拉自锁式 |
| 工作温度 | -55°C~+125°C |
| 最大潮湿 | 在60°C/140°F时最高达到95% |
| 屏蔽性能 | 75dB(10MHz) 40dB(1GHz) |
| 抗振动性能 | 15g[10Hz~2000Hz] |

| 特性 | 参数 |
|-------|----------|
| 盐雾试验 | 96hr |
| 抗冲击性能 | 100g,6ms |
| 机械寿命 | 5000次 |
| 防护等级 | IP68 |

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | |
|------------------------|----------------|------------------|------------------|
| DRAWN BY: Jack Lu | DATE: 12/13/19 | MAT'L | TITLE: CONNECTOR |
| CHECKED BY: Jacky Chen | DATE: 12/13/19 | FINISH | MODLE: Z1插座 |
| APPROVED BY: Tony Kao | DATE: 12/13/19 | SCALE: 1:1 | DWG NO. |
| | | SHEET NO: 1 of 1 | PART NO. |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|-------|------|
| | | | |

SIZE: A4
VER: R1