



项目		尺寸(mm)									面板开孔尺寸(mm)		
系列	型号	A	B	L	N	M	E	S1	S4	e	Ws	Ø	种类
00B	Z3	8.5	10	15.9	13.7	2.5	4.0	6.3	7.5	M7*0.5	6.4	7.1	A
0B	Z3	11	12	22	16.8	2.5	2.5	8.2	9	M9*0.6	8.3	9.1	A
1B	Z3	14	16	24	18.7	3.2	5.0	10.5	12	M12*1.0	10.6	12.1	A
2B	Z3	18	20	27.5	20	3.5	4.5	13.5	15	M15*1.0	13.6	15.1	A
3B	Z3	21.8	23	31	25	4.0	9.0	16.5	20	M18*1.0	16.6	18.1	A
4B	Z3	28	30	37	29	4.5	9.5	23.5	26	M25*1.0	23.6	25.2	A

产品主要技术参数

特性	参数
锁紧方式	推拉自锁式
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19		MODLE	Z3插座
CHECKED BY:	DATE	FINISH	DWG NO.	
Jacky Chen	12/13/19		PART NO.	
APPROVED BY:	DATE	SCALE	1:1	
Tony Kao	12/13/19	SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4
VER R1