



项目		尺寸(mm)								面板开孔尺寸(mm)		
系列	型号	A	B	L	M	E	S1	S2	e	Ws	Ø	种类
0B	Z6	10	12.5	20	9.8	3.5	8.2	11	M9*0.6	8.3	9.1	A
1B	Z6	14	16.0	19.5	11	4	10.5	14	M12*1.0	10.6	12.1	A
2B	Z6	18	19.2	24	12	5.1	13.5	17	M15*1.0	13.6	15.1	A

### 产品主要技术参数

特性	参数	特性	参数
锁紧方式	推拉自锁式	盐雾试验	96hr
工作温度	-55°C~+125°C	抗冲击性能	100g,6ms
最大潮湿	在60°C/140°F时最高达到95%	机械寿命	5000次
屏蔽性能	75dB(10MHz) 40dB(1GHz)	防护等级	IP68
抗振动性能	15g[10Hz~2000Hz]		

东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	Z6插座
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE  
A4  
VER  
R1