



项目		尺寸(mm)									面板开孔尺寸(mm)		
系列	型号	A	B	L	E	M	S1	S2	S3	e	Ws	Ø	种类
0B	Z9	10	12.3	35.5	7	1.2	11	8	8.2	M9*0.6	8.3	9.1	A
1B	Z9	14	16	40.5	7.5	1.5	14	9	10.5	M12*1.0	10.6	12.1	A
2B	Z9	18	19.2	47	8.5	2	17	13	13.5	M15*1.0	13.6	15.1	A
3B	Z9	21	25	56	11.5	2	22	15	16.5	M18*1.0	16.6	18.1	A

产品主要技术参数

特性	参数
锁紧方式	推拉自锁式
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY: Jack Lu	DATE: 12/13/19	MAT'L	TITLE: CONNECTOR
CHECKED BY: Jacky Chen	DATE: 12/13/19	FINISH	MODLE: Z9插座
APPROVED BY: Tony Kao	DATE: 12/13/19	SCALE: 1:1	DWG NO.
		SHEET NO: 1 of 1	PART NO.

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE: A4
VER: R1