

## BZE F系列插座防尘盖

壳体材料：黄铜镀镍  
O形密封圈：硅橡胶  
防水等级：IP67

挂绳材料：不锈钢  
最高工作温度：135°


产品编号	系列	尺寸 (mm)			
		A	B	D	N
BZF.102F.CSS-100	102F	16.5	9	9	100
BZF.103F.CSS-100	103F	19.8	12	14	100
BZF.1031F.CSS-100	1031F	18.4	13	14	100
BZF.104F.CSS-150	104F	21	15	16	150
BZF.105F.CSS-150	105F	24	18	20	150

### JX/DB系列金属连接器技术特性

机械寿命：5000~10000次  
最大潮湿：在60°C时最高达到95%  
屏蔽性能：75dB(10MHz) 40dB(1GHz)  
抗振动性能：15g[10Hz~2000Hz]  
盐雾试验：96hr  
抗冲击性能：100g,6ms  
防护等级：IP68  
工作温度：-55°C~+125°C

 **东莞市高迪电子有限公司**  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	BZE
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/13/19	1:1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R1