



**MICRO USB公/USB2.0公成型直式插头(卡扣式)**  
**MICRO USB Male to USB 2.0 Male Overmolded Cable(Bayonet)**

**E10B - M UM - MWA / M U2 - NWA - 1 PV - S**



线长(M): 1:1M 2.5:2.5M .....	线材: PV:PVC PU:PU	空:非屏蔽 S:屏蔽
-------------------------------------	------------------------	---------------

**产品参数** PRODUCT PARAMETERS

壳体材料 Shell material	高性能工程塑料/金属+塑胶 High performance engineering plastics /Metal+Plastic	插入损耗 Insertion Loss	≤0.2dB
阻燃等级 Flame retardant grade	UL94-V0	回波损耗 Return Loss	≥50dB
连接方式 Termination	焊接式/压接式/快速插拔连接 Welding/ Crimping/Quick plug connect	适用温度 Working temperature	-25°C ~ +85°C
防水等级 Waterproof level	IP67, IP68	传输速率 Baud rate	≈20000000Mbit/s

**东莞市高迪电子有限公司**  
**DONG GUAN GAO DI ELECTRONICS CO., LTD**

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19		MODLE	E10B - M UM - MWA-A
CHECKED BY:	DATE	FINISH	DWG NO.	SIZE
Jacky Chen	12/13/19		PART NO.	A4
APPROVED BY:	DATE	SCALE	1 : 1	VER
Tony Kao	12/13/19	SHEET NO.	1 of 1	R1

ITEM NO.	DESCRIPTION	DRAWN	DATE