



HDMI 公弯头/公直式带线插头(螺纹式) HDMI R/A Male to Str.Male Cable plug(Threaded)

E13T - M H4 - MWD / NWA - 1 PV - S

规格:
H2:HDMI 2K
H4:HDMI 4K
H8:HDMI 8K

线长(M): 1:1M 2.5:2.5M	线材: PV:PVC PU:PU PE:PE	空:非屏蔽 S:屏蔽
-------------------------------------	---------------------------------	---------------



产品参数 PRODUCT PARAMETERS

塑料材料 Plastic Material	PA66, 尼龙, 增强尼龙, 硅胶 PA66, Nylon, Reinforced Nylon, Silicone	绝缘电阻 Insulation resistance	≥100 mΩ DC500V
金属材料 Metal Material	铜镀金 Copper gold-plated	接触电阻 Contact resistance	30 mΩ
连接方式 Coupling	螺纹锁紧(T);卡扣锁紧(B) Thread (T); Bayonet(B)	适用温度 Applicable temperature	-40°C ~ +105°C
接线方式 Termination way	焊接、焊板 Solder, Welding plate	额定电流 Rated current	50 mA
插拔次数 Durability	≥500次(Cycles)	防水等级 Waterproof grade	IP67

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu	DATE 12/13/19	MAT'L	TITLE CONNECTOR
CHECKED BY: Jacky Chen	DATE 12/13/19	FINISH	MODLE E13T - M H4 - MWD
APPROVED BY: Tony Kao	DATE 12/13/19	SCALE 1 : 1	DWG NO.
		SHEET NO. 1 of 1	PART NO.

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE
A4
VER
R1