



E16USB 公/公成型直式插头(卡扣式)

E16USB Male to Male Overmolded with Cable(Bayonet)

E16B - M U2 - MWA / NWA - 1 PV - S

规格:
U2: USB 2.0
U3: USB 3.0

线长(M):
1:1M
2.5:2.5M
.....

线材:
PV:PVC
PU:PU

空:非屏蔽
S:屏蔽

产品参数 PRODUCT PARAMETERS

壳体材料 Shell material	高性能工程塑料/金属+塑胶 High performance engineering plastics /Metal+Plastic	插入损耗 Insertion Loss	≤0.2dB
阻燃等级 Flame retardant grade	UL94-V0	回波损耗 Return Loss	≥50dB
连接方式 Termination	焊接式/压接式/快速插拔连接 Welding/Crimping/Quick plug connect	适用温度 Working temperature	-25°C ~ +85°C
防水等级 Waterproof level	IP67, IP68	传输速率 Baud rate	≈200000000Mbit/s

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu	DATE 12/13/19	MAT'L	TITLE CONNECTOR
CHECKED BY: Jacky Chen	DATE 12/13/19	FINISH	MODLE E16B - M U2 - MW
APPROVED BY: Tony Kao	DATE 12/13/19	SCALE 1:1	DWG NO.
		SHEET NO. 1 of 1	PART NO.
			SIZE A4
			VER R1

ITEM NO.	DESCRIPTION	DRAWN	DATE