



成型式针型直式插头
EDB2 Straight Male Overmolded Plug

EDB2 - M 15 - MWA 14 - 1 PV - S

芯数:
15
26H
3W3
3W3C
7W2
11W1

大针线规:
14:14AWG
10:10AWG
08:8AWG
06:6AWG(默认)
空:小针

线长(M):
1:1M
2.5:2.5M
.....

线材:
PV:PVC
PU:PUR/TPU
PE:PE
TF:铁氟龙

空:非屏蔽
S:屏蔽



产品参数 PRODUCT PARAMETERS

| | | | |
|-------------------------------|-----------------|--------------------------------|----------------|
| 额定电流 Rated current | 10A/20A/30A/40A | 插拔力 Plug and unplug force | 符合IEC60807-3 |
| 额定电压 Rated voltage | 1000 V | 接线范围 Wire bound | 8mm~14mm |
| 耐电压 Withstand Voltage | 500 V | 插拔次数 Durability | ≥500次(Cycles) |
| 绝缘阻抗 Insulation resistance | 5000 MΩ | 适用温度 Applicable temperature | -55°C ~ +105°C |
| 接触阻抗 Contact resistance | 10 mΩ | 防水等级 Waterproof grade | IP65/IP67 |

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | | |
|--------------|----------|-----------|----------|---------------------------------|
| DRAWN BY: | DATE | MAT'L | TITLE | CONNECTOR |
| Jack Lu | 12/13/19 | | | |
| CHECKED BY: | DATE | FINISH | MODLE | EDB2 - M 15 - MWA 14 - 1 PV - S |
| Jacky Chen | 12/13/19 | | | |
| APPROVED BY: | DATE | SCALE | DWG NO. | SIZE |
| Tony Kao | 12/13/19 | 1 : 1 | | A4 |
| | | SHEET NO. | PART NO. | VER |
| | | 1 of 1 | | R1 |