

IP50

系列	壳体号	ØA	L	M	S1Y	S2Y
00S	P01	6.4	26	18	6	4.5
0S	P01	9	34.5	24.5	7	6.4
1S	P01	12	42.5	31.5	9	8.5
2S	P01	14.8	52	40	12	11


S系列金属连接器技术特性

机械寿命：	> 5000次	盐雾试验：	96hr
最大潮湿：	在60°C时最高达到95%	抗冲击性能：	100g, 6ms
屏蔽性能：	75dB(10MHz) 40dB(1GHz)	防护等级：	IP50
抗振动性能：	15g[10Hz~2000Hz]	工作温度：	-55°C~+125°C


东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	P01
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1 : 1		
		SHEET NO.	PART NO.	
		1 of 1		

SIZE
 A4
 VER
 R1