



# IP50


系列	壳体号	ØA	L	H	S1Y
00S	P02	7.7	25.1	18.5	7
0S	S02	11	30	23	9
1S	S02	13.5	37	30.5	12

## S系列金属连接器技术特性

机械寿命：	> 5000次	盐雾试验：	96hr
最大潮湿：	在60°C时最高达到95%	抗冲击性能：	100g, 6ms
屏蔽性能：	75dB(10MHz) 40dB(1GHz)	防护等级：	IP50
抗振动性能：	15g[10Hz~2000Hz]	工作温度：	-55°C~+125°C

 **东莞市高迪电子有限公司**  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	P02
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/13/19	1:1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R1

ITEM NO.	DESCRIPTION	DRAWN	DATE