



系列	壳体号	ØA	L	S1Y	S2Y
0S	S05	8.9	33.5	7	4.5
1S	S05	11.9	40.5	9	8.5
2S	S05	14.8	50	12	11

IP50

S系列金属连接器技术特性

- 机械寿命: >5000次
- 最大潮湿: 在60°C时最高达到95%
- 屏蔽性能: 75dB(10MHz) 40dB(1GHz)
- 抗振动性能: 15g[10Hz~2000Hz]
- 盐雾试验: 96hr
- 抗冲击性能: 100g,6ms
- 防护等级: IP50
- 工作温度: -55°C~+125°C

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	S05
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/13/19	1:1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R1

ITEM NO.	DESCRIPTION	DRAWN	DATE