

IP50


系列	壳体号	ØA	L	S1Y	S2Y
00S	S05	6.4	25	6	4.5
0S	S05	9	33.5	7	6.4
1S	S05	12	40.5	9	8.5
2S	S05	14.8	50	12	11.5

S系列金属连接器技术特性

机械寿命：	>5000次	盐雾试验：	96hr
最大潮湿：	在60°C时最高达到95%	抗冲击性能：	100g,6ms
屏蔽性能：	75dB(10MHz) 40dB(1GHz)	防护等级：	IP50
抗振动性能：	15g[10Hz~2000Hz]	工作温度：	-55°C~+125°C

 **東莞市高迪電子有限公司**
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	S05
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1 : 1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE
A4
VER
R1