



### S07

外装内固定通用型插座，机箱外螺母固定，定位销(G)或定位销(A---M)

系列	壳体号	ØA	ØB	L	M	E	S1Y	S3Y	e
00B	S07	10	10.2	15.9	2.5	4.3	6.3	9	M7*0.5
0B	S07	12	12.5	21.3	2.5	5.5	8.2	11	M9*0.5
1B	S07	16	16.0	23.2	3.2	6.0	10.5	14	M12*1.0
2B	S07	20	19.2	24.8	3.5	6.5	13.5	17	M15*1.0
3B	S07	23	25.4	30.7	4.0	11.5	16.5	22	M18*1.0

### T系列金属连接器技术特性

- 机械寿命： >5000次
- 最大潮湿： 在60°C时最高达到95%
- 屏蔽性能： 75dB(10MHz) 40dB(1GHz)
- 抗振动性能： 15g[10Hz~2000Hz]
- 盐雾试验： 96hr
- 抗冲击性能： 100g,6ms
- 防护等级： IP66~IP68
- 工作温度： -55°C~+125°C



TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	S07
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE