



系列	壳体号	J	I	H	Ød	Øb	D	L	B	ØA	N	R
00B	S10	18.5	5	3.5	0.7	0.5	11.5	18.5	8.9	6.8	7.5	5.08
0B	S10	25.5	3	6.7	0.7	0.6	14.6	25.5	13.3	9	11.7	7.62
1B	S10	26.8	3	7.5	0.7	0.6	16.67	26.8	13.3	11	12.6	7.62

T系列金属连接器技术特性

机械寿命：	>5000次	盐雾试验：	96hr
最大潮湿：	在60°C时最高达到95%	抗冲击性能：	100g,6ms
屏蔽性能：	75dB(10MHz) 40dB(1GHz)	防护等级：	IP66~IP68
抗振动性能：	15g[10Hz~2000Hz]	工作温度：	-55°C~+125°C


东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°
 3RD. ANGEL'S
 UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	S10
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1 : 1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE