



GD-TX-2+9M 插座

注释:

1. 特性:

- 额定电压 : DC 500V
- 额定电流 : 3A-20A
- 温度范围 : -20C° ~+125C°

2. 材料:

- 胶芯 : PA66+25% G.F(UL94V-0)-WH
- pin针 : 黄铜, 镀金

3. 注意事项:

- a. 盐雾测试过12H不能有氧化生锈现象
- b. 成品不能有缺PIN, 孔位不一致等不良。



TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	3RD. ANGEL'S	UNITS	MM
	Above 5 ~ 15 ±0.3			
	Above 15 ~ 30 ±0.4			
	Above 30 ~ 50 ±0.5			
	Angle ±0.3°			

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-TX-2+9-11
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE	A4
VER	R1