



主要技术特性要求:

- 使用条件:
环境温度: -30~80℃
相对湿度: 90% (55℃)
- 额定负荷: DC60V 25A (大针) 12A (中针)
- 接触电阻: ≤10mΩ
- 绝缘电阻: ≥100MΩ
- 耐压: AC700V (50Hz) 1min
- 插拔力: ≤80N
- 寿命: 3000次
- 盐雾试验: 48 hour
- 面板螺丝锁紧扭力: 0.25N.M

序号	零件料号	名称	材料	数量	镀层/颜色	备注
⑤		冠簧	铍铜Be2.0	2	镀金	
④		母小插簧	磷铜QSn4-3	4	镀金	
③		母中插簧	黄铜HPb59	2	镀金	
②		母大插簧	黄铜HPb59	2	镀金	
①		基座	PA66, UL94 V-0	1	黑色	

 **东莞市高迪电子有限公司**
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-AC-DCD-27-224-M母座
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
SHEET NO.	1 of 1	PART NO.		