

**主要技术特性要求:**

**1. 使用条件:**

环境温度: -25~70℃

相对湿度: 90% (40℃)

**2. 额定负荷: DC300V 30A**

**3. 接触电阻: ≤10mΩ**

**4. 绝缘电阻: ≥1000MΩ**

**5. 耐压: AC2000V (50Hz) 1min**

**6. 插拔力: 20~60N**


**7. 寿命: 3000次**

**8. 盐雾试验: 72 hour**

6	——	加长小插簧	黄铜HPb59	1	镀金1u"	
5	——	小插簧	黄铜HPb59	4	镀金1u"	
4	——	中插簧	黄铜HPb59	1	镀金1u"	
3	——	大插簧	黄铜HPb59	2	镀金1u"	
2	——	冠簧	镀青铜	2	镀金1u"	
1	——	基座	PA66, UL94 V-0	1	黑色	
序号	零件料号	名称	材料	数量	镀层/颜色	备注

 **东莞市高迪电子有限公司**  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-AC-DCD-M23-2+1+5-M
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/13/19	1:1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R1