



技术要求:

- 1、额定负荷: DC70V 15A
- 2、接触电阻: $\leq 0.03 \Omega$
- 3、绝缘阻抗: $\geq 100M \Omega$
- 4、耐 压: AC500V (50HZ)/min
- 5、插 拔 力: 10~35N (1.0KGf以上)
- 6、寿命: 1500次
- 7、符合: ROHS2.0、REACH、Prop 65

2	绝缘体	114-001	PA66+30%GF	黑色	UL 94V-0
1	中心针	32-200197-01-G	黄铜HBI59-1	镍>80U"金1U"	2
项目	零件名称	料号	材料	处理	数量

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-TX-2050-G
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
SHEET NO.	1 of 1	PART NO.		

SIZE
A4
VER
R1