


- 主要技术特性要求:
1. 环境温度: $-25\sim 80^{\circ}\text{C}$
 2. 额定电流: 2A
 3. 接触电阻: $\leq 20\text{m}\Omega$
 4. 绝缘电阻: $\geq 20\text{M}\Omega$
 5. 耐压: 200V AC (50Hz) 1min
 6. 插拔力: 10~35N
 7. 公母对插寿命: ≥ 300 次
 8. 符合RoHS2.0及其修订指令要求
 9. 未注尺寸公差按GB/T14486-2008 MT5
 10. 阻燃符合UL94-V0

3	8.510.0054	长冲针	1	冲压成型	C5191磷青铜	前金后锡镀金部 $0.5\mu\text{m}$	借用XH-207BM
2	8.510.0053	短冲针	7	冲压成型	C5191磷青铜	前金后锡镀金部 $0.5\mu\text{m}$	借用XH-207BM
1	8.005.0270	基座	1	注塑成型	PBT+GF15%	黑色	
序号	零件图号	零件名称	数量	工艺类别	材料/规格型号	表面处理	备注

 **东莞市高迪电子有限公司**
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	± 0.2
Above 5 ~ 15	± 0.3
Above 15 ~ 30	± 0.4
Above 30 ~ 50	± 0.5
Angle	$\pm 0.3^{\circ}$

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-TX-Y807-M
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE	A4
VER	R1