


主要技术特性要求:

1. 环境温度: -25~80°C
2. 额定电流: 2A
3. 接触电阻: ≤20mΩ
4. 绝缘电阻: ≥20MΩ
5. 耐压: 200V AC (50Hz) 1min
6. 插拔力: 10~35N
7. 公母对插寿命: ≥300次
8. 符合RoHS2.0及其修订指令要求
9. 未注尺寸公差按GB/T14486-2008 MT5
10. 阻燃符合UL94-V0

序号	零件图号	零件名称	数量	工艺类别	材料/规格型号	表面处理	备注
4	8.370.0019	O型密封圈	1	模压成型	硅橡胶 $\phi 5 \times \phi 0.7$	红色	独立包装出货
3	8.510.0679	长针	1	车削加工	Hpb59-1黄铜	镀金1 $\mu$ "	借用XH-Y807AG
2	8.510.0678	短针	8	车削加工	Hpb59-1黄铜	镀金1 $\mu$ "	借用XH-Y807AG
1	8.005.0443	底座	1	注塑成型	PBT+GF15%	黑色	

 **東莞市高迪電子有限公司**  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5  $\pm 0.2$   
 Above 5 ~ 15  $\pm 0.3$   
 Above 15 ~ 30  $\pm 0.4$   
 Above 30 ~ 50  $\pm 0.5$   
 Angle  $\pm 0.3^\circ$

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19	FINISH	MODLE	GD-TX-Y907-G
CHECKED BY:	DATE	SCALE	DWG NO.	SIZE
Jacky Chen	12/13/19	1:1	PART NO.	A4
APPROVED BY:	DATE	SHEET NO.		VER
Tony Kao	12/13/19	1 of 1		R1