



主要技术特性要求:

1. 使用条件:
 环境温度: -25~70°C
 相对湿度: 95% (40°C)
2. 额定负荷: DC500V 15A (瞬间30A)
3. 接触电阻: ≤20mΩ
4. 绝缘电阻: ≥500MΩ
5. 耐压: AC5000V (50Hz) 1min
6. 插拔力: 10~80N
 单一插拔力: 3~20N
7. 寿命: 5000次
8. 盐雾试验: 72 hour

2	320833	母端子	QSn6.5-0.1y t=0.6	5	镀镍
1	310546	基座	PA66, UL94 V-0	1	黑色
序号	零件料号	名称	材料	数量	镀层/颜色

东莞市高迪电子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19	FINISH	MODLE	GD-TX-07-500F
CHECKED BY:	DATE	SCALE	DWG NO.	SIZE
Jacky Chen	12/13/19	1:1		A4
APPROVED BY:	DATE	SHEET NO.	PART NO.	VER
Tony Kao	12/13/19	1 of 1		R1