



- 主要技术特性要求:
1. 环境温度: -25~80°C
 2. 额定电流: 电源Pin: 28A; 信号Pin: 2A
 3. 接触电阻: ≤20mΩ
 4. 绝缘电阻: ≥20MΩ
 5. 耐压: 500V AC (50Hz) 1min
 6. 插拔力: 20~80N
 7. 公母对插寿命: ≥2000次
 8. 符合RoHS2.0及其修订指令要求
 9. 未注尺寸公差按GB/T14486-2008 MT5
 10. 阻燃符合UL94-V0

序号	零件图号	零件名称	数量	工艺类别	材料/规格型号	表面处理	备注
4	8.370.0026	密封垫	1		硅橡胶	白色透明	
3	8.510.0235	大针	2	车削加工	Hpb59-1黄铜	镀金1μ"	
2	8.510.0236	小针	3	车削加工	C54400磷青铜	镀金1μ"	
1	8.005.0252	底座	1	注塑成型	PA66+GF30%	黑色	

东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	12/13/19			
CHECKED BY:	DATE	FINISH	MODLE	GD-TX-R525AM
Jacky Chen	12/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/13/19	1:1		
SHEET NO.	1 of 1	PART NO.		
				SIZE A4
				VER R1