



P.C.B LAYOUT MOUNTING PATTERN

## SPECIFICATIONS

### Electrical:

- 1.Current Rating: 1.0A / contact terminal
- 2.Voltage Rating: 30V DC
- 3.Contact Resistance: 50 milliohms Max
- 4.Dielectric Withstanding Voltage: 300 V AC AT Sec Level
- 5.Insulation Resistance: 100 MEGA ohms Min

### Mechanical:

- 1.Connector Mate and Unmate Force  
Mate force: 3.0 kgf (Max)  
Unmate force: 0.7 kgf (Min)
- 2.Terminal Retention: 0.5 kgf (Min)

### Material:

- 1.Housing: High Temperature Thermal Plastics, UL 94V-0 , LCP , Black
- 2.Contact: Phopshor Bronze
- 3.Shell: Brass

### Finish:

- 1.Contact: Plated Gold in Mating Area ; Gold Plated on Solder Balls ; Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer

 東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu  
CHECKED BY: Jacky Chen  
APPROVED BY: Tony Kao

DATE: 10/24/13  
DATE: 10/24/13  
DATE: 10/24/13

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO USB 5PF B TYPE 沉板0.7mm
SCALE	1 : 1	DWG NO.	MRUSB-5B-M3-S175
SHEET NO.	1 of 1	PART NO.	MRUSB-5B-M3-S175
		SIZE	A4
		VER	R1

1	更新鍍層	Jack	102413
ITEM NO.	DESCRIPTION	DRAWN	DATE