


1. Functional spec.	
1.1 Rated Voltage	AC125V 3A / AC250V 1.5A
1.2 Contact Resistance	≤100mΩ
1.3 Operating Force	130 ± 30 gf
1.4 Free Position	7.35 ± 0.2 mm
1.5 Operating Position	7.0 ± 0.2 mm
2. Reliable Rating	
2.1 Mechanical Life	1000,000 CYCLES
2.2 Electrical Life	10,000 / 1,000,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC500V
2.4 Withstand Voltage	AC500V 1 minute
2.5 Soldering Temper	250°C Max 3 Sec.
2.6 Operating Temper	-25°C ~ +65°C
2.7 Ambient Humidity Used	<85%RH

### SCHEMATIC



 東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/09/15		MODLE	MICRO SWITCH
CHECKED BY:	DATE	SCALE	DWG NO.	DM3-00P
Jacky Chen	12/09/15	1 : 1	PART NO.	DM3-00P
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	12/09/15			

3	更新Rated Voltage	Jack	120915
2	圖面標示更新	Jack	031714
1	圖面更新	FrankWu	120211
ITEM NO.	DESCRIPTION	DRAWN	DATE