


P.C.B LAYOUT MOUNTING



SCHEMATIC

1. 功能規格			
1.1 額定電壓	125VAC/250VAC; 3A/1.5A	1.5 自由位置 (FP)	10.4 ± 0.8mm
		1.6 動作位置 (OP)	8.8 ± 0.8mm
1.2 接觸電阻 (CR)	≤ 100mΩ (初始值)	1.7 行程 (PT)	
1.3 操作力 (OF)	10~25 gf	1.8 靈敏度 (BT)	
1.4 回彈力 (RF)			
2. 可靠度參數			
2.1 機械壽命	500,000 CYCLES	2.5 焊接方式	手工焊
2.2 電器壽命	10,000 CYCLES	2.6 適用溫度	-25° C ~ +65° C
2.3 絕緣電阻	≥ 100MΩ DC500V (初始值)	2.7 適用濕度	< 85%RH
2.4 耐壓強度	AC500V 1 minute (初始值)		

東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	10/31/13			
CHECKED BY:	DATE	FINISH	MODLE	MICRO SWITCH
Jacky Chen	10/31/13			
APPROVED BY:	DATE	SCALE	DWG NO.	DM3-01P-15
Tony Kao	10/31/13	1 : 1	PART NO.	DM3-01P-15
		SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE