


1. Functional spec.	
1.1 Rated Voltage	125/250VAC
1.2 Rated Current	5A
1.3 Contact Resistance	$\leq 50m\Omega$ (Initial value)
1.4 Operating Force	115 \pm 30gf
1.5 Free Position	11.9 \pm 0.3mm
1.6 Operating Position	11.3 \pm 0.35mm
2. Reliable Rating	
2.1 Mechanical Life	100,000 CYCLES
2.2 Electrical Life	10,000 CYCLES
2.3 Insulation Resistance	$\geq 100M\Omega$ DC500V(Initial value)
2.4 Withstand Voltage	AC1,000V 1 minute (Initial value)
2.5 Soldering Temper	250 °C Max 3 Sec.
2.6 Operating Temper	-15 °C - +70 °C
2.7 Shipping Temper	-25 °C - +85 °C
2.8 Ambient Humidity Used	<85%RH

SCHMATIC



 東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Frank Wu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 11/07/11
DATE: 11/07/11
DATE: 11/07/11

MAT'L		TITLE	SWITCH
FINISH		MODLE	MICRO SWITCH
SCALE	1 : 1	DWG NO.	SM5-00N
SHEET NO.	1 of 1	PART NO.	SM5-00N
		SIZE	A4
		VER	A

ITEM NO.	DESCRIPTION	DRAWN	DATE