

P.C.B MOUNTING PATTERN


SPECIFICATIONS

- 1. Rating : DC 30V 0.1A
- 2. Circuit : 2P2T
- 3. Timing : Non-Shorting
- 4. Operating force : 250 ± 100gf
- 5. Life test : 10,000 cycles

NOTE:

- 1. PS-D12L-S191: SELF-LOCK
- 2. PS-D12NL-S191:NON-LOCK

- 3. Timing : Non-Shorting
- 4. Operating force : 250 ± 100gf
- 5. Life test : 10,000 cycles



SCHEMATIC

| NO. | DESCRIPTION | QTY | MATERIAL | REMARK |
|-----|---------------|-----|-----------------|-----------|
| 6 | CONTACT(CLIP) | 2 | PHOSPHOR BRONZE | Ag-Plated |
| 5 | SPRING | 1 | SUS | |
| 4 | TERMINAL | 6 | BRASS | Ag-Plated |
| 3 | CASE | 1 | PBT | BLACK |
| 2 | COVER | 1 | POM | WHITE |
| 1 | KNOB | 1 | POM | BLUE |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-----------------|-------|--------|
| 5 | 更新圖面 | Jack | 041322 |
| 4 | 更新KNOB顏色 | Jack | 032322 |
| 3 | 更新COPING CASE材質 | Jack | 032222 |
| 2 | 新增SPEC | Jack | 102315 |
| 1 | 新增PIN編號 | Jack | 101215 |



TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | | |
|--------------|----------|-----------|----------|--------------|
| DRAWN BY: | DATE | MATL | TITLE | SWITCH |
| Jack Lu | 04/13/22 | | MODLE | PUSH SWITCH |
| CHECKED BY: | DATE | FINISH | SCALE | 1 : 1 |
| Jacky Chen | 04/13/22 | | DWG NO. | PS-D12x-S191 |
| APPROVED BY: | DATE | SHEET NO. | PART NO. | PS-D12x-S191 |
| Tony Kao | 04/13/22 | 1 of 1 | | |

| | |
|------|----|
| SIZE | A4 |
| VER | R5 |