



SPECIFICATIONS

- 1.RATING: DC 5.0V,1.0mA ; DC 3.0V,1.0uA
- 2.CONTACT RESISTANCE: 3Ω Max.
- 3.INSULATION RESISTANCE: 100MΩ Min.
- 4.WITHSTAND VOLTAGE: AC 100V/ MINUTE.
- 5.OPERATING FORCE: 35gf Max.
- 6.OPERATING LIFE CYCLE: 50,000 CYCLES.

6	SPACER	1	PA46	
5	TERMINAL	1	PBS	Ag plating
4	HOUSING	1	LCP	
3	CONTACT FORM	1	PBS	Ag plating
2	COVER	1	SUS	
1	STEM	1	PA46	
NO	PART NAME	QTY	MATERIAL	REMARK

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	01/09/20		MODLE	DETECTOR SWITCH
CHECKED BY:	DATE	FINISH	SCALE	1 : 1
Jacky Chen	01/09/20		DWG NO.	DS-C51E-S138
APPROVED BY:	DATE	SHEET NO.	PART NO.	DS-C51E-S138
Tony Kao	01/09/20	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE