


P.C.B LAYOUT

SPECIFICATIONS

Rating	DC 12V, 0.1A.
Contact Resistance	100mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	40±10 gf
Mechanical Life	20,000 cycles



7	PRESS HANDLE	PA66	1	BLACK
6	CONTACT POINT	Ag	1	
5	CONTACT	BeCu	1	
4	KNOB	PA66	1	WHITE
3	COVER	PA66	1	BLACK
2	TERMINAL	BRASS	3	Ag PLATED
1	BASE	PA66	1	BLACK
NO	NAME	MATERIAL	QTY	FINISHING

4	更新Mechanical Life	Jack	102423
3	更新材質表	Jack	110322
2	更新圖面	Jack	061121
1	更新料號	Jack	050521
ITEM NO.	DESCRIPTION	DRAWN	DATE

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	10/24/23			
CHECKED BY:	DATE	FINISH	MODLE	MICRO SWITCH
Jacky Chen	10/24/23			
APPROVED BY:	DATE	SCALE	DWG NO.	SSM-001A-40-S379
Tony Kao	10/24/23	1 : 1		
		SHEET NO.	PART NO.	SSM-001A-40-S379
		1 of 1		
				SIZE A4
				VER R5