


P.C.B LAND PATTERN



CIRCUIT DIAGRAM


SPECIFICATIONS

Rating	50mA 12V DC
Insulation Resistance	100MΩ Min.
Dielectric Withstanding Voltage	AC 250 V
Contact Resistance	100mΩ Max.
Operating Force	2 160 ± 50gf 3 260 ± 50gf
Operating Life(cycles)	70,000

D	FILM	1		
C	CONTACT	1	SUS	Ag plated
B	BASE	1	LCP(Black)	
A	THERMINAL	4	PHOSPHOR BRONZE	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

 東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 - 15 ±0.3
Above 15 - 30 ±0.4
Above 30 - 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/30/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH
Jacky Chen	12/30/22			
APPROVED BY:	DATE	SCALE	DWG NO.	TS-A96-x-S410
Tony Kao	12/30/22	1 : 1		
		SHEET NO.	PART NO.	TS-A96-x-S410
		1 of 1		

1	更新PIN編號位置	Jack	123022
ITEM NO.	DESCRIPTION	DRAWN	DATE