



***MATERIAL**

- TERMINAL 1 :PHOSPHOR BRONZE
- TERMINAL 2 :PHOSPHOR BRONZE
- TERMINAL 3 :PHOSPHOR BRONZE
- TERMINAL 4 :PHOSPHOR BRONZE
- TERMINAL 5 :PHOSPHOR BRONZE
- TERMINAL 10 :BRASS
- TERMINAL 11 :BRASS
- HOUSING : PA6T

SPECIFICATION

- 1.Rating : DC 12V 1.0A
- 2.Contact resistance : ≤50mΩ
- 3.Insulation resistance : ≥100MΩ
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles

MODEL NO.	PJ-3827D	PJ-3825D
SCHEMATIC		



TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	11/03/15		MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-382xD
Jacky Chen	11/03/15	1 : 1	PART NO.	PJ-382xD
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	11/03/15			

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	110315
1	更新圖面	Jack	041614