



APPLICABLE FFC

NOTES:

1. MATERIAL:

HOUSING: LCP,UL 94-V0,COLOR:NATURE
 ACTUATOR: LCP,UL 94-V0,COLOR:BLACK
 CONTACT: PHOSPHOR BRONZE
 LEG: BRASS

2. PLATING:

CONTACT: GOLD OR TIN PLATED ON NICKEL OVERALL
 LEG: TIN PLATED ON NICKEL OVERALL

3. RATING:

CURRENT RATING: 0.4A AC/DC
 VOLTAGE RATING: 50V AC/DC
 TEMPERATURE RANGE: -25°C ~ +85°C

PIN NO.	DIM. A	DIM. B	DIM. C
04	8.60	3.00	5.07
05	9.60	4.00	6.07
06	10.60	5.00	7.07
07	11.60	6.00	8.07
08	12.60	7.00	9.07
09	13.60	8.00	10.07
10	14.60	9.00	11.07
11	15.60	10.00	12.07
12	16.60	11.00	13.07
16	20.60	15.00	17.07
20	24.60	19.00	21.07
26	30.60	25.00	27.07

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	新增PIN選項	Jack	081224
4	更新樣式	Jack	042522
3	更新樣式	Jack	031919
2	新增插入深度尺寸	Jack	081117
1	新增10PIN選項	Jack	120816



TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	08/12/24	FINISH	MODLE	FPC 1.0mm 前掀 H:1.53mm
CHECKED BY:	DATE	SCALE	DWG NO.	FPC10L-15xx-B-S304
Jacky Chen	08/12/24	1 : 1	PART NO.	FPC10L-15xx-B-S304
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	08/12/24			

SIZE	A4
VER	R5