



(Number of Conductors) N	X
(Pitch) P	0.50mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

規格 (Spec)	0.5×X×X×C1 (X/X/X/X) (0.035×0.3) (0.06+0.06)UL20624		
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06(白/印字 white/printed)	
2	下絕緣膠 (Under Insulation)	0.06(白 white)	
1	導體 (Conductor)	0.035×0.3 (鍍錫 Tin Plating)	
ITEM	DESCRIPTION	SPECIFICATION	REMARK

ITEM NO.	DESCRIPTION	DRAWN	DATE

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 - 15 ±0.3
 Above 15 - 30 ±0.4
 Above 30 - 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	FFC CABLE
Jack Lu	11/27/15	FINISH	MODLE	FFC CABLE
CHECKED BY:	DATE	SCALE	DWG NO.	FC11-xxx-S281
Jacky Chen	11/27/15	SHEET NO.	PART NO.	FC11-xxx-S281
APPROVED BY:	DATE			
Tony Kao	11/27/15			

SIZE A4
VER R